



TimberVu W-Series Doors (W200)

The artistic fusing of an architectural aluminum exterior with the classic look and feel of a natural wood interior provides the ageless charm found only in TimberVu W-Series Doors.

Duality by design, the melding of these complimentary materials offer the chance to customize your living space and visually share the timeless comfort seen throughout the broad spectrum of contemporary architectural planning.



Available in Swing or Sliding operational styles along with sidelites, transoms and multiple mulling configurations.

Unique to the market, the SolidCore™ Thermal Barrier System integrates an Azo-Core high-density foam that acts as an insulator against the natural conductivity of heat and cold, allowing for superior energy performance and product integrity regardless of size or operational style.



TimberVu W-Series Swing Door (W200) Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
 - 4-9/16" and 6-9/16" Jamb Depths
 - 5-5/8" Frame Depth
- SolidCore™ Technology - Door Panels
- OptiCore® Technology - Frame
- Pine Interior
- Corner Key Technology for Maximum Structural Performance
- Adjustable Butt Hinges Offers Multi-Directional Adjustment
- Butt Joint Panels
- Wide and Narrow Panel Options
- Available as an Inswing or Outswing
- Raised Profile and Applied Grid Capabilities
- Standard, ADA and No Sill Options
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Swing Door Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	30"	43"	78"	120"	180"
Two Panel - French	48"	84"	78"	120"	216"
Sidelight - Narrow	15"	108"	78"	120"	191"
Sidelight - Fixed Panel Set	24"	108"	78"	120"	191"
Transom	12"	120"	12"	108"	191"

Swing Door Performance		
Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	.024 - .029
Two Panel - French	R-50 / LC-50	.024 - 0.29
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	

TimberVu W-Series Sliding Door (W200) Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
 - 4-9/16" and 6-9/16" Jamb Depths
 - 5-5/8" Frame Depth
- SolidCore™ Technology - Door Panels
- OptiCore® Technology - Frame
- Pine Interior
- Corner Key Technology for Maximum Structural Performance
- 2 and 4 Panel Operation Availability
- Square and Beveled Glazing Options
- Extruded Fin
- Raised Profile and Applied Grid Capabilities
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Sliding Door Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	95"	78"	120"	264"
Four Panel	120"	193"	78"	120"	408"
Sidelight - Narrow	12"	108"	78"	120"	191"
Sidelight - Fixed Panel	24"	108"	78"	120"	191"
Transom	12"	120"	12"	108"	191"

Sliding Door Performance		
Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	.026 - .031
Four Panel	R-50 / LC-50	.026 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	



Quaker Window Products
 504 U.S. Hwy 63 South
 Freeburg, MO 65035
 (800) 347-0438
www.quakerresidentialwindows.com

Discover More Here :

