

EdgeVu Windows (H450)



Architecturally Elegant

Architecturally elegant, where sleek lines and oversized glass gives access to the brilliance of the outside world.



Steel Replica Windows

Designed to bring light and life deeper into your home, this distinct collection of Windows draws upon the traditional look of steel while offering an alternative of architectural aluminum.



Redefining Engineering Limitations

Replicating the look of steel, EdgeVu Windows have been engineered to meet the strictest building codes regardless of region or climate.



Superior Structuraral Performance

Designed to match the iconic look of historical windows and drawn to define the contemporary feel of today's trends, EdgeVu takes modern technological advances and intertwines them in a proprietary frame design to provide a base for Superior Performance and Product Flexibility.

Superior Structural Performance - Energy Efficient - Maintenance Free

EdgeVu Window (H450) Highlights, Performance and Operation

- Patented OptiCore Technology Framing System
 - 3-1/4" Extruded Aluminum Frame
 - 1-3/8" Sightlines Fixed
 - 2-1/4" Sightlines Vent
- Dual Euro-Groove Frame System to Improve Water and Wind Performance
- Sealant Injected Double Corner Key Frame Design Technology Offers Maximum Structural Performance
- Azo-Core Thermal Barrier System for Increased Energy Efficiency and Reduced Thermal Conductivity
- Multiple Glazing Package Options Compliment Regionality and Climate
- Structural Mull Availability Offers Wider and Taller Sizing Options
- Internal or Simulated Divided Lights (SDLs) Available

Window Sizing									
Operation	Wic	ith	Height						
	Min	Max	Min	Max					
Direct Set	10"	120"	10"	120"					
Casement	24"	48"	18"	84"					
Casement Push-Out	24"	36"	18"	84"					
Awning	20"	72"	18"	84"					
Single Hung	17"	72"	30"	132"					

Window Performance								
Operation	Rating	Structural Load (P.S.F.)	Air Infiltration	Water (P.S.F.)	U-Value	SHGC		
Direct Set	AW-110	110.3	0.01	15.04	0.26 - 0.31	0.24 - 0.37		
Casement	CW-80	80.2	0.12	12.11	0.39 - 0.43	0.21 - 0.32		
Casement Push-Out	CW-80	80.2	0.12	12.11	0.39 - 0.43	0.21 - 0.32		
Awning	CW-80	80.2	0.12	12.11	0.40 - 0.60	0.21 - 0.32		
Single Hung	AW-PG50	50.12	0.1	10.66	≤ 0.30	0.21 - 0.32		

Interior & Exterior Color Options





Quaker Window Products 504 U.S. Hwy 63 South Freeburg, MO 65035 (800) 347-0438

www.quakerresidentialwindows.com

Discover More Here:

